



Color Coated Lead

bleiCOLOR
bleiCOLOR-SK



ISO TS 16949 for the
Area of Application:
Manufacture and Sale of
Battery Terminals
for Lead Accumulators



RÖHR + STOLBERG GmbH . Bruchfeld 52 . 47809 Krefeld
Phone ++49 (0)21 51-58 92-0 . Fax ++49 (0)2151-50 0270
vertrieb@roehr-stolberg.de . www.roehr-stolberg.de

bleiCOLOR

DP Nr. 2737151.3 is used for the composition of **bleiCOLOR**

Standard sizes:

Rolls of

1,25 X	150 X	12000 mm
1,25 X	250 X	7000 mm
1,25 X	330 X	5000 mm
1,25 X	450 X	4000 mm
1,25 X	1000 X	3500 mm

Other sizes are available on request

Standards colors:

Brick red/brown
Reddish brown/black grey

Colors:

- Brick red similar to RAL 8004
- Brown similar to RAL 8019
- Black grey similar to RAL 7021
- Reddish brown similar to RAL 8012

The lead is painted on both sides to match existing substrate.

The use of lead for roof and wall applications has a long tradition. A combination of special lead properties like corrosion properties, high impermeability, great ductility and the case of recycling have made lead as a material, the answer to so many problems in the present day. With its color coated surfaces **bleiCOLOR** offers greater aesthetic design freedom in these roof and wall applications to both architects and tradesmen.

The advantages of bleiCOLOR:

- The paint finish allows perfect match with existing roof and wall colors
- UV-resistant
- Paint resists high temperatures
- Readily recycled

Laying advice: To prevent possible expansion fractures, individual lengths should not exceed 1 metre at a time.

Applications:



Dormer ready prepared for cladding



Closure and seal to the sides with **bleiCOLOR**

bleiCOLOR-SK

The perfect self-adhesive metal sheet for all flashings and seals.

How long a building can resist weather and environmental influences depends on the quality of the construction materials. **bleiCOLOR-SK** is a material suitable for the high demands of traditional craftsmen, enabling both fast and therefore economic use.

bleiCOLOR-SK is a totally self-adhesive metal sheet for all flashings and seals on roofs. It is especially suitable for sealing the roof to features such as chimneys etc. The colour of the coated surfaces suites all commonly used roofing colours, is long lasting resistant, and does not loose its attractiveness.



Dormer window connections with flashing

Technical information:


bleiCOLOR-SK is supplied in coils of 5 metres length, 300 and 450 mm wide. The material is available coloured brick red, brown, black grey or reddish brown. Special colours can be supplied upon request. The minimum working temperature must be 0° Celsius.

The advantages of bleiCOLOR-SK

- UV-resistant
- Perfect self-adhesive for fast use
- Long lasting, attractive, and high quality colour coating
- Long lasting metal solution for high quality demands
- Easily shaped, long lasting, and flexible in all weather conditions
- Highly suitable for flashings



Lengthening the material



Removing the protection foil



Sticking and shaping



Chimney sealed with flashing