

bleiCOLOR Dry Ridge Vent Roll

The double-sided colour-coated, corrugated lead sheet for sealing all typical ridge and hip tiles



Lead sheet with environmental product declaration



Institut Bauen und Umwelt e.V.



DIN EN ISO 9001:2008
DIN EN ISO 14001:2004
OHSAS 18001:2007





RÖHR + STOLBERG GmbH . Bruchfeld 52 . 47809 Krefeld
Tel. +49 (0) 21 51-58 92 - 0 . Fax +49 (0) 21 51-50 02 70
rs-vertrieb@roehr-stolberg.de . www.roehr-stolberg.de

dealer's stamp

bleiCOLOR Dry Ridge Vent Roll for sealing all typical ridge and hip tiles

bleiCOLOR ridge and hip seal



No glueing in the ridge and hip area!

Standard dimensions

280 x 5.000 mm

320 x 5.000 mm

Special dimensions on request

Colour combinations

 tile red / brown

 tile red / dark grey

Special colours available on request

Aeration cross-section

approx. 150 cm²/metre laid
(sufficient for a rafter length of 15 m as per DIN 4108)

bleiCOLOR Dry Ridge Vent Roll is an all-metal solution for sealing all typical ridge and hip tiles. The universal dry fixed ventilated ridge and hip system is the perfect complement to the bleiCOLOR branded product range.

bleiCOLOR Dry Ridge Vent Roll guarantees permanent ventilation as well as being quick and easy to install. The vent openings meet the DIN standard and are designed to keep out moisture, insects and to resist blockages due to dirt. The pleating makes the material easy to shape and matches the finish of the tiles. The lead sheet is coated in two colours and can be worked on both sides.

Advantages

- quick and easy installation
- can be installed in damp conditions
- easily handled, shaped and flexible
- no special tools required for cutting
- simple fixing instructions using nails/tacks
- durable and UV, wind and temperature resistant
- two-colour design for use either way up, colour-matched to all common roof colours
- excellent recyclability

Service

Röhr + Stolberg is an experienced provider of lead products with extensive knowledge of all sectors and state of the art production facilities. Our aspiration is to offer our customers a unique and personal service in all areas. We therefore arrange training courses and support our customers by providing advice on the in installation of our products.

Instructions for Installation



Freewheeling on the ridge



Nail in the middle or tack in place



Shape, no glueing required