



bleiCOLOR

DRY RIDGE VENT ROLL

Colour-coated lead sheet for sealing ridge and hip tiles.

bleiCOLOR DRY RIDGE VENT ROLL

Long-lasting ridge and hip tile sealing

All-rounder for roofs and façades.

Lead sheet is one of the most traditional materials used for roofs and façades. Extremely durable, one hundred percent recyclable and offering outstanding cold-forming properties, it has been the material of choice for sustainable construction for centuries.

Specialist for ridge and hip tiles

bleiCOLOR Dry Ridge Vent Roll was specially developed for sealing all typical ridge and hip tiles. The full-metal solution consists of a single lead sheet, giving it an extended service life. Its high intrinsic weight renders the edges extremely resistant to wind uplift – flapping due to adhesive fatigue is thus excluded.

Flexible fitting without the need for adhesive

Since no adhesive is required to fix bleiCOLOR Dry Ridge Vent Roll, it can be fitted in any weather and at any temperature. Once unrolled on the ridge, bleiCOLOR Dry Ridge Vent Roll only needs to be fixed to the apex using nails or tacks and then formed. The corrugated sheets are elastic at the expansion zones and can be formed individually. The perforation ensures reliable aeration in accordance with DIN 4108 (Part 3).

Coated on both sides

The UV- and weather-resistant coating ensures a uniform, long-lasting finish that harmonises with the roof colour. The sheets are supplied with a two-colour coating so that they can be laid on either side.

STANDARD DIMENSIONS

280 x 5,000 mm

320 x 5,000 mm

Colour combinations

 **Brick red / brown**
similar to RAL 8004/8019

 **Brick red / charcoal grey**
imilar to RAL 8004/7021

Other colours are available on request.

Aeration cross-section

as per DIN 4108 (Part 3)
approx. 150 cm/metre laid,
sufficient for a rafter length of 15 m

Also available

bleiCOLOR
Colour-coated lead sheet for roofs and façades

bleiCOLOR-SK
Self-adhesive, colour-coated lead sheet



A step up in service and quality: Röhr + Stolberg is Germany's foremost company in the field of lead processing. Customers benefit from our advice on lead applications and our training courses on lead working. Its long service life, high recycling rate of nearly one hundred percent and the minimal energy consumed in its production make lead the perfect material for sustainable construction.

RÖHR + STOLBERG GmbH
Bruchfeld 52 | 47809 Krefeld
Germany
Tel. +49 (0) 21 51 - 58 92 - 0
Fax +49 (0) 21 51 - 50 02 70
rs-vertrieb@roehr-stolberg.de
www.roehr-stolberg.de



Institut Bauen
und Umwelt e.V.
DIN EN ISO 9001:2008
DIN EN ISO 14001:2004
OHSAS 18001:2007

**A plus for the environment –
recyclable lead sheet**

 Dealer's stamp

